

MEDIAGUARD[®] RACK SLEEVE

Server Rack Decommissioning Made Easy



ACCEPTABLE MEDIA



42U Server
Rack



45U Server
Rack



48U Server
Rack

How it Works:

The MediaGuard® Rack Sleeve slips over a fully populated server rack and tightens down with a tamper-proof ratchet system for a snug, secure fit. One technician can deploy it in minutes. Reinforced nylon and tamper-evident tabs keep the rack sealed through transport and storage, and the sleeve is fully reusable, so it goes back into rotation instead of the landfill.

Key Features & Benefits:

- **Customizable fit.** Fits any standard server or network rack, with custom sizing available.
- **One-person deployment.** Lightweight and quick for a single technician to install.
- **Reusable and trackable.** Built for repeated use, with optional tracking for secure transport and audit trails.
- **Secure ratchet-tightening system.** Tamper-proof ratchet mechanism locks in a tight fit around the rack.
- **Durable nylon construction.** Reinforced stitching and tamper-evident tabs prevent unauthorized access.
- **Better visibility and handling.** Clearly marked grab points make racks safer and easier to maneuver.
- **Minimizes tripping hazards.** Unlike plastic wrap, these sleeves stay secure and contained.





9001 | 14001 | 45001

MEDIAGUARD® Rack Sleeve

Secure Rack Decommissioning

Secure, reusable protection for fully populated server racks.

Specifications:

Media Accepted

Compatible with standard 19" (482.6 mm) EIA-310-D server racks in 42U, 45U, and 48U configurations. Suitable up to depth of 1,000 mm.

Weight (excludes packing and crating)

5.5 lbs. (2.5 kg)

Shipping Weight

7 lbs. (3.2 kg)

Dimensions

43" x 25" x 80" (109.5 cm x 63.5 cm x 203.5 cm) (L x W x H)

Shipping Dimensions

15" x 6" x 14" (38 cm x 15.5 cm x 36 cm) (L x W x H)

Compliance

Supports ISO/IEC 27001 compliance as a transport and storage security control.



Safety

Durable nylon sleeve with reinforced stitching and tamper-evident tabs to prevent unauthorized access.

Secure ratchet-tightening system - tamper-proof ratchet mechanism ensures a tight and secure fit around the rack.

Sustainability / Longevity

Reusable & trackable - built for repeated use. Helps achieve ESG goals.

Temperature

59 - 500 °F (15 - 260°C)



Real people. Real help.
24/7 nationwide and worldwide.





TRUSTED BY INDUSTRY LEADERS WORLDWIDE:

FORTUNE 500 COMPANIES

GOVERNMENT ENTITIES

FINANCIAL INSTITUTIONS

ITAD PROVIDERS

GLOBAL ENTERPRISES

NIST
SP 800 - 88

ISO
9001 | 14001 | 45001

DIN
66399



GET IN TOUCH:

www.phiston.com | +1 305-517-1744 | info@phiston.com