

MEDIAFLUX[®] DEGAUSSER

Powerful. Compliant. Built for High-Throughput Degaussing.



ACCEPTABLE MEDIA



HDD



ENTERPRISE-HDD



USB/ FLASH DRIVE




PHONES



CD/DVD



TAPES



CIRCUIT BOARDS

How it Works:

Powered by a minimum 2.2 Tesla magnetic flux field, the MediaFlux® fully degausses HDDs and magnetic media in under 30 seconds at a rate of up to 120 drives per hour. Degaussed drives are automatically collected in the built-in debris drawer, making it a fully automated, hands-off solution for offices and data centers.

Key Features & Benefits:

- **Fully sanitizes** drives in less than 30 seconds.
- **Fully automated, hands-off operation** for user safety.
- **Universal power input** for global clients.
- **Comes standard** with a debris door.
- **No special adapters needed** for power or for degaussing various media.
- **RFI and EMI suppression** minimizes interference with nearby electronic equipment.
- **Can be paired with the MediaVise® Compact Combo Destroyer** for a complete colo or small workplace data destruction solution.

DESTRUCTION MECHANISM

Degaussing

2.2 Tesla minimum magnetic flux field.



MEDIAFLUX®

High-volume, compliant HDD degausser



1- Feed Port

2-Touchscreen

3- Debris Drawer



NIST
SP 800 - 88

ISO
9001 | 14001 | 45001

DIN
66399

Compact Yet Powerful

A high-power desktop degausser ideal for offices, data centers, and compliance-driven environments.

MEDIAFLUX Degausser

Specifications:

Media Accepted	HDD, Enterprise HDD, USB/Flash, Tapes (LTO & DLT), Cell Phones, DVDs, Circuit Boards
Magnetic Force	2.2 Tesla minimum.
Hourly Throughput	120 drives per hour.
Cycle Time	15 seconds per drive.
Waste Collection	Built-in debris drawer, holds up to 25 HDDs
Media Feeding	Gravity-assisted, top-loaded manual feed port, 6" x 4" (15.5 cm x 10.5 cm), one device at a time



Dimensions / Weight

17" x 24" x 16"
(43 cm x 61 cm x 40 cm) (L x W x H)
160 lbs. (72 kg)

Electrical Power

28 Amps (peak) at 110-120 Volts A.C., 1-phase, 50/60 Hz
9 Amps (peak) at 220-230 Volts A.C., 1-phase, 50/60 Hz

Operating Temperature

40-100°F (4-37.8°C)



Real people. Real help.
24/7 nationwide and worldwide.





TRUSTED BY INDUSTRY LEADERS WORLDWIDE:

FORTUNE 500 COMPANIES

GOVERNMENT ENTITIES

FINANCIAL INSTITUTIONS

ITAD PROVIDERS

GLOBAL ENTERPRISES



GET IN TOUCH:

www.phiston.com | +1 305-517-1744 | info@phiston.com