

MEDIAVISE[®] COMPACT HDD DESTROYER

Powerful. Compact. Uncompromising Security for Your Data.



ACCEPTABLE MEDIA



HDD



ENTERPRISE-HDD



USB/ FLASH DRIVE



PHONES



CD/DVD

How it Works:

Powered by Phiston's proprietary hydraulic crushing system, the MVC-HDD delivers 20 tons (40,000 lbs) of destructive force to crush and demolish every square inch of the HDD's magnetic data storage platters, controller, and read heads in under 30 seconds, with destroyed media ejected directly into the included collection bin for completely hands-off operation.

Key Features & Benefits:

- **NSA/CSS approved** for the secure destruction of HDDs.
- **Fully sanitizes drives** in less than 30 seconds.
- **Fully automated, hands-off operation** for user safety.
- Media destruction performed in-house so media never leaves your custody intact.
- **Comes standard with a debris door.** Optional debris chute available for continuous discharge into any recycle bin.
- **No special adapters needed** for power or for crushing various media.
- **Crushing plates never need to be sharpened** or replaced.
- **RFI and EMI suppression** minimizes interference with nearby electronic equipment.

DESTRUCTION MECHANISM

Hydraulic Crushing

20 tons (40,000 lbs) of destructive force.



①

1- Feed Port

②

2- Control Panel

③

3-Debris Drawer



MVC-HDD

NSA/CSS Approved



MVC-HDD MEDIAVISE® COMPACT HDD DESTROYER

Uncompromising Destruction

The NSA/CSS-approved compact HDD destroyer is deployable in any office, data center, or truck.

Specifications:

Media Accepted

HDD and Enterprise HDD (HAMR, MAMR, EAMR, Hybrid), Cell Phones, Circuit Boards, PDAs, DVD/Blu-Ray.

Media Sanitization Modality

Hydraulic crushing, 20 tons (40,000 lbs) of destructive force.

Hourly Throughput

120 drives per hour.

Cycle Time

30 seconds per drive.

Waste Collection

Collection bin holds 1 computer HDD or 2 laptop HDDs. Optional chute for continuous discharge.

Media Feeding

Gravity-assisted, top-loaded manual feed port, 5.75" x 1.25" x 4" (15 cm x 3 cm x 10 cm), one device at a time



Dimensions / Weight

16" x 22.5" x 9.75" / 41 cm x 57 cm x 25 cm
(H x L x W) · 130 lbs. (59 kg)
130 lbs. (59 kg) 110V model
145 lbs. (66 kg) 220V model

Electrical Power

220 Volts A.C. ±10%, 50/60 Hz, 7.5 Amps 110 Volts A.C. ±10%, 50/60 Hz, 15 Amps
Factory configured for any international power supplies

Operating Temperature

40-100°F (4-37.8°C)



Real people. Real help.
24/7 nationwide and worldwide.



TRUSTED BY INDUSTRY LEADERS WORLDWIDE:

FORTUNE 500 COMPANIES

GOVERNMENT ENTITIES

FINANCIAL INSTITUTIONS

ITAD PROVIDERS

GLOBAL ENTERPRISES

NIST
SP 800 - 88

ISO
9001 | 14001 | 45001

DIN
66399



GET IN TOUCH:

www.phiston.com | +1 305-517-1744 | info@phiston.com